

Via Caduti della Liberazione, 57 21040 Uboldo (VA) – Italia Tel: +39 02 964121 Fax: +39 02 96412294

Web: www.eurocel.it

# PRODUCT INFORMATION EUROCEL 733 GDA/S

### **DESCRIPTION**

Double sided adhesive tape.

### **PRODUCT DATA**

Backing	Cotton cloth	
Adhesive	Synthetic rubber and resins; transparent	
Liner	Double sided siliconized paper; white	

	Unit	Value	Method
Total thickness (without Liner)	mm	0.250	PSTC 133
Adhesion to steel	N/25mm	Int: 30 – Ext: 25	PSTC 101
Tensile strength MD	N/25mm	62.5	PSTC 131
Elongation at break	%	5	PSTC 131
Temp. Resistance	°C	60°C	=

### **APPLICATION**

Standard double sided carpet tape, given its high tack and adhesive mass, it is the best choice for working on rough flooring. Plasticizers resistant version of the Eurocel 730 GDA.

Features	Benefits			
Synthetic rubber and resins adhesive	<ul> <li>✓ High level of tack and adhesion on both sides</li> <li>✓ Excellent adhesion on rough surfaces</li> <li>✓ Plasticizers resistant</li> <li>✓ Suitable for most kind of carpets</li> </ul>			
Cotton cloth backing	✓ Highly adaptable to various shapes ✓ Hand tearable			

## **CONDITIONS OF USE AND CONFORMITY**

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.