

Via Caduti della Liberazione, 57 21040 Uboldo (VA) – Italia Tel: +39 02 964121 Fax: +39 02 96412294 Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL MSK 6280

DESCRIPTION

Masking tape for automotive body shops.

PRODUCT DATA

Backing	58 g/m² natural saturated crepe paper; white	
Adhesive	Natural rubber and resins solvent based	

	Unit	Value	Method
Total thickness	mm	0.130	PSTC 133
Adhesion to steel	N/25mm	4.5	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	8.5	PSTC 131
Temp. Resistance	°C	80°C (100°C x 30min)	=

APPLICATION

Masking tape suitable for high performance application for use in automotive repair workshops.

Features	Benefits		
Natural rubber and resins solvent based adhesive	 ✓ Easy removal without adhesive residue ✓ Good adhesion even on irregular surfaces ✓ Excellent resistance to paint and lacquer thinners ✓ Heat resistant up to 100°C (30 min) 		
Saturated paper backing	 ✓ Well conformable to most surfaces ✓ Removable without breaking ✓ Compatible with most common ✓ Hand tearable paints and lacquers 		

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.